Technical Specifications

Double[®] 3

Work even better from anywhere.

Hardware

Cameras

- 2 x 13 Megapixel Unified Pan/Tilt/Zoom Module
- One super wide angle lens, one super zoom lens
- 30 FPS and Night Vision Mode

Sensors

- 2 x Stereovision depth sensors (Intel[®] RealSense[™] D430) 5 x Ultrasonic range finders
- 2 x Wheel encoders (2048 PPR each)
- 1 x Inertial Measurement Unit (9 DoF)

Processors, Memory, and Storage

- NVIDIA[®] Jetson[™] TX2-4GB System-on-Module
- 256-core NVIDIA[®] Pascal[™] GPU Architecture
- Dual-core NVIDIA® Denver 2 64-Bit CPU
- Quad-core ARM[®] A57 Complex
- 4GB 128-bit LPDDR4 Memory
- 16GB eMMC 5.1 Flash Storage

Battery

4 hours of runtime, 2 hour recharge time Li-ion



Audio

6 x Digital microphones with beamforming 8-watt full range speaker

Display

9.7-inch LED-backlit multi-touch LCD Remotely-adjustable height (47" to 60" tall)

Wireless Connectivity

Wi-Fi - Intel Dual-Band Wireless-AC (2.4GHz, 5GHz) Bluetooth 4.2

Developer Expansion

2 x USB 3.2 SuperSpeed ports HDMI video output port Top and rear hardware mounting points

Colors

User-replaceable silicone trim (5 colors available)

Software

Video Protocol WebRTC 128-bit AES encrypted

Supported Driver Interfaces

Mac or Windows PC with Chrome, Firefox, or Safari iPad and iPhone, or Android with Chrome

Fleet Management

Enterprise-level adminstrative tools

Developer API Available

Brought to you in India by VirtuLab & Artiligent virtuLab@designdesk.in



Doublerobotics.com